

Wednesday Gasifier Training Problem Part 1: Project Setup

February 2018

CPFD Software LLC
10899 Montgomery Blvd. NE, Suite A
Albuquerque, NM 87111
+1.505.275.3849
www.cdfd-software.com


Training Objectives

- This training exercise adds more realism and complexity to the gasifier model defined yesterday.
 - More internal geometries are included: gas sparger and heating coils
 - Injection points are added to introduce fresh coal and steam into the system
 - Chemistry and thermal calculations are added
 - BC Connection filters are used for advanced post-processing
- Set up a complex model based on a previously defined simplified model.
 - Copy a project file to a new location using **Save Case As...**
 - Modify the grid as necessary
 - Adjust boundary condition definitions as necessary
 - Add chemistry and thermal definitions to project
- Use several newly introduced features of Barracuda.
 - Thermal calculations
 - Injection BCs
 - Chemical reactions

Process Sheet


- Thermal calculations are enabled, initial temperature of particles and gas in bed set to 1300 K.
- Chemical reactions are included.

Boundary	Fluid Flow	Particle Flow
Fluidizing Air	Mass flow rate = 0.691 kg/s Temperature = 700 K Gas (mass fractions): 0.77 N ₂ , 0.23 O ₂	None
Steam Sparger through 204 injection nozzles	Mass flow rate = 0.296 kg/s Velocity = 10 m/s Temperature = 900 K Gas: pure H ₂ O	None
Fresh Coal Feed	Mass flow rate = 5 g/s Velocity = 5 m/s Temperature = 500 K Gas (mass fractions): 0.77 N ₂ , 0.23 O ₂	Fresh coal at 1 kg/s
Cyclone Diplegs	Velocity = 0.5 m/s Temperature = 1300 K Gas: pure N ₂	Cyclone dipleg particles with flow rate set to match elutriation into each cyclone.



Particle Properties

- Initial bed particles:
 - Assumed to be already devolatilized.
 - Particle composition (mass fractions): 0.8999 Carbon (s), 0.1 Ash (s), and 0.0001 Volatiles (g)
 - PSD will be same as Tuesday Gasifier with name "psd_initial_char_in_bed.sff".
- Fresh coal particles:
 - Multi-material including volatiles which are released.
 - Particle composition (mass fractions): 0.45 Carbon (s), 0.05 Ash (s), 0.5 Volatile
 - Volatile composition (mass fractions): 0.4144 CH₄, 0.1702 CO, 0.0444 CO₂, 0.111 H₂, 0.26 H₂O
 - PSD will be same as Tuesday Gasifier with name "psd_fresh_coal_feed_particles.sff".
- Cyclone dipleg particles:
 - Composition, temperature, and PSD will be automatically determined by BC Connection.



For material properties, assume that the fresh coal particles have a density of 1450 kg/m³ and that the initial bed and cyclone dipleg particles have a density of 725 kg/m³

Chemical Reactions


Reaction	Stoichiometric Equation	Reaction Rate Expression (mol m ⁻³ s ⁻¹)	Source
Steam gasification	C(s)+H ₂ O → CO+H ₂	$r_{1,f} = 6.36m_c T \exp\left(\frac{-22,645}{T}\right)[\text{H}_2\text{O}]$	Syamlal, 1992
	CO+H ₂ → C(s)+H ₂ O	$r_{1,r} = 5.218 \times 10^{-4} m_c T^2 \exp\left(\frac{-6,319}{T} - 17.29\right)[\text{H}_2][\text{CO}]$	
CO ₂ gasification	C(s)+CO ₂ → 2CO	$r_{2,f} = 6.36m_c T \exp\left(\frac{-22,645}{T}\right)[\text{CO}_2]$	Syamlal, 1992
	2CO → C(s)+CO ₂	$r_{2,r} = 5.218 \times 10^{-4} m_c T^2 \exp\left(\frac{-2,363}{T} - 20.92\right)[\text{CO}]^2$	
Methanation	0.5C(s)+H ₂ → 0.5CH ₄	$r_{3,f} = 6.838 \times 10^{-3} m_c T \exp\left(\frac{-8,078}{T} - 7.087\right)[\text{H}_2]$	Syamlal, 1992
	0.5CH ₄ → 0.5C(s)+H ₂	$r_{3,r} = 0.755m_c T^{0.5} \exp\left(\frac{-13,578}{T} - 0.372\right)[\text{CH}_4]^{0.5}$	
Combustion	2C(s)+O ₂ → 2CO	$r_4 = 4.34 \times 10^7 \theta_c T \exp\left(\frac{-13,590}{T}\right)[\text{O}_2]$	Yoon, 1978
Water gas- shift	CO+H ₂ O → CO ₂ +H ₂	$r_{5,f} = 7.68 \times 10^{10} \exp\left(\frac{-36,640}{T}\right)[\text{CO}]^{0.5}[\text{H}_2\text{O}]$	Bustamante, 2005
	CO ₂ +H ₂ → CO+H ₂ O	$r_{5,r} = 6.4 \times 10^9 \exp\left(\frac{-39,260}{T}\right)[\text{H}_2]^{0.5}[\text{CO}_2]$	Bustamante, 2004

What do we want to learn from this model?

- Always keep in mind why you are running any model.
- For the previous, simplified gasifier training problem, we wanted to learn the following:
 - General fluidization characteristics
 - Entrainment rate of particles
- For this more complex model, we would like to additionally study:
 - Are there any hot-spots in the bed?
 - What is the gas composition leaving the cyclones?
 - Did the addition of thermal and chemistry affect the conclusions drawn based on studying results of the simplified model?


More Complex Geometry

- To create the CAD for this complex geometry, the solid parts shown here were created.




Final STL File with Internal Structures Subtracted

- The cyclones, gas sparger, and heating coils were subtracted from the vessel.
- The example here was made with AutoDesk Inventor, using a “Derived Part” based on an assembly of the individual parts.
- This resulted in a solid model of the internal flow volume in which particles and fluid can travel.
- Remember: we need a model of the interior flow volume. We do not want a “thin-walled” geometry.




Copy Tuesday Gasifier project using "Save Case As..."

- Open the Tuesday gasifier project with Barracuda VR.
- Use the Barracuda GUI menu **File** → **Save Case As...**
- For the Target Directory, navigate to and select **5_Wednesday_Gasifier/my_setup**





Selecting Files in the **Save Case As...** Dialog

- A full Barracuda VR project setup includes the base project file (*.prj), the geometry (*.stl), transient boundary condition files (*.sff), particle size distribution files (*.sff), and potentially other files as well.
- The **Save Case As...** dialog allows you to select exactly which files you want to include or exclude during the copy operation.
- For the current case, keep:
 - Project Files
 - sff Files
 - Script Files
- Because the Wednesday Gasifier geometry is different, do not keep:
 - STL Files
 - Grid Files
- Also, we don't want to copy over any results files (Flux, Transient, or GMV).



Gridding: Add the New STL File


- In the **Setup Grid** section, highlight “gasifier_tuesday.stl” and click **Remove**.
- Click **Add** and select the new geometry, “gasifier_wednesday.stl”.
- There are more internals in the current STL file than in the Tuesday Gasifier.
- Use **Set uniform grid**, and change the total number of cells to 100,000. Be sure to click on **Keep all current major grid lines**, so that grid lines for the cyclone horns and diplegs are not lost
- If you generate the grid now, you can inspect the STL geometry using **View Output** → **View CAD**.
- Using **View Output** → **View Transparent Model**, you can see the regions that need attention during gridding.



Modify the Grid to Capture Internal Structures

- With this geometry, and with most real systems, you will not be able to capture everything perfectly.
- Instead, try to capture everything fairly well, without completely missing any structures.
- The heating coils are too small to capture using grid lines on all sides. Instead, use the “cross” strategy of intersecting grid lines inside the heating coils.
- The sparger arms are big enough that you should be able to hit most of them with grid lines on all sides.
- As guidelines, here are the number of real and null cells in the grids for the pre-setup versions of the Tuesday and Wednesday gasifiers:

Tuesday: 28,556
Wednesday: 119,658




At left is a view of the pre-setup grid, using the built-in shortcut **View Output, View Transparent Model**. Notice that not all of the geometry is perfectly captured. But, it is possible to not completely miss any of the internal structures.

Tip: To facilitate checking the transparent model during gridding, save the attribute file by clicking on **File → Put attributes**.

Show your final grid to the instructor before proceeding to further project setup.


Enable Thermal Flow

- In the **Global Settings** section, choose the **Thermal Flow** radio button to enable thermal calculations.
- It is possible to delay the start of thermal calculations by using the **Start with Thermal: Off** option. However, for this training exercise, we will **Start with thermal: On**.
- The **Heat transfer coefficients** button can be used to adjust the heat transfer coefficients between wall-and-fluid and particles-and-fluid (defaults used here).
- When enabling thermal calculations, it is important to check your **Base Materials** section to make sure all materials have valid thermal properties.
- Thermal conductivity, specific heat, and viscosity are all described by various methods in Barracuda VR. It is important that these methods are valid within the temperature range expected in the simulation.
- Start with chemistry “On”.




Automated Plotting of Polynomial Material Properties

- This feature allows users to plot the expressions (Polynomial (4th order), Double Polynomial, Interpolated from SFF File) for property data in **Base Materials**.
- Users can visualize property data over a range of temperatures present within a simulation.
- To view the plot for the polynomial, click on the **Plot** button in the GUI.




Temperatures of Initial and Boundary Conditions

- When the Tuesday gasifier was set up as isothermal, it was not important to consider the temperature specifications for initial and boundary conditions.
- However, when turning on thermal calculations, it is important to review the settings (some of them may have been initialized to default values by Barracuda VR), and apply correct temperatures to all initial and boundary conditions.
- One particular item to check is the initial condition temperature of the fluid and particles. Barracuda VR initializes this to 300 K by default, which will cause extreme heat transfer difficulties during start-up of this hot gasifier if it is not corrected.
- Initialize the system to a **Temperature** of “1300” K.



Fresh Coal Feed Injection

- Instead of using a flow boundary on a face to introduce fresh coal into the system, we will use an injection BC.
- This allows for injection of fluid and/or particles at a specific angle and location in the system.
- Before creating this injection BC, delete the fresh coal feed flow BC from the project.



Fresh Coal Feed Injection

- Click on **Injection BC**:
 - The Injection BC page allows for the injection of fluid and/or particles to be specified at a given location, velocity, mass flow rate, and direction
 - One or more injection sets may be created in a project file and each injection set may consist of one or more injection point locations
 - Injection points within an injection set will have a common composition and velocity
 - Each injection set can have:
 - Particle or Tracer injection alone
 - Fluid injection alone
 - Both particle/tracer and fluid injection
- Click on **Add**.
- Start by entering an **Injection Name** and **Flux Plane**.

The screenshot shows the 'Injection BC Editor' window. The 'Injection name' field is circled in red and contains 'Fresh_coal_feed'. The 'Flux plane name' field is also circled in red and contains 'FLUXBC_fresh_coal_feed'. The 'Injection type' is set to 'Particle'. The 'Locations' table has one row with 'nz' as the name and 'Off' as the status. The 'Add' button at the bottom is highlighted with a red arrow.

Name	On/Off	X (m)	Y (m)	Z (m)	nx	ny
1	<input type="checkbox"/> Off					

Fresh Coal Feed Injection

- Select **Particle/tracer Injection**.
- Use a transient (.sff) file to specify the particle mass flow rate:
 - Click on **Edit**
 - Enter the appropriate values
 - **Save** the file using a descriptive name
- Select **Particle** and **Fresh coal feed** from the pull down menus for **Type** and **Species**.
- Set the **Angle Expansion** to “15”.

Injection BC Editor

Injection name: Fresh_coal_feed

Comment:

Particle/Tracer Injection

Use BC Connector data

Use file article_injection.sff **Edit**

Use specified values

Injection type

Type: Particle

Species: 002 - fresh coal feed

Velocity: 0 m/s

Mass flow: 0 kg/s

Temperature: 0 K

Number density: 125

Angle Expansion

θ_{E1} : 15 θ_{E2} : 15

Angle Orientation

α_{E1} : 0

Locations (0 of 0 injections are active)

Name	On/Off	X (m)	Y (m)	Z (m)	nx	ny	nz	Particle Mass Weight	Particle Temp Multiplier
1	<input type="checkbox"/> Off								

Flux plane options

Flux plane name: FLUXBC_fresh_coal_feed

Gas species flux plane behavior: No Output

Subdivide by radius Radius divisions: 100

Output raw particle data

Fluid Injection

Use BC Connector data

Use file

Use specified values

Velocity: 0 m/s

Mass flow: 0 kg/s

Temperature: 0 K

Fluid composition

Define fluids

Locations (0 of 0 injections are active)

Particle weight sum: 0

Buttons: Add Row, Delete Row, Check Table, Import, Export

Particle Injection Boundary Conditions Editor

Time (s)	On/Off	Temperature (K)	Velocity (m/s)	Mass Flow Rate (kg/s)	Number Density Manual
1 0	<input checked="" type="radio"/> On	500	5	1	1000
2	<input checked="" type="radio"/> On				

Buttons: Add Row, Delete Row, Check Data, Graph, Update Simulation

File: fresh_coal_feed_particle_injection.sff **Save** Save As Close

Fresh Coal Feed Injection

- Select **Fluid Injection**.
- Use a transient (.sff) file to specify the fluid mass flow rate:
 - Click on **Edit**
 - Enter the appropriate values
 - **Save** the file using a descriptive name
- Specify the **Fluid Composition**.

Injection BC Editor

Injection name: Fresh_coal_feed

Comment:

Particle/Tracer Injection

Use BC Connector data

Use file `article_injection.sff` **Edit**

Use specified values

Injection type

Type: Particle

Species: 002 - fresh coal feed

Velocity: 0 m/s

Mass flow: 0 kg/s

Temperature: 0 K

Number density: 125

Angle Expansion: θ_{E1} 15 θ_{E2} 15

Angle Orientation: α_{E1} 0

Flux plane options

Flux plane name: FLUXBC_fresh_coal_feed

Gas species flux plane behavior: No Output

Subdivide by radius (Radius divisions: 100)

Output raw particle data

Fluid Injection

Use BC Connector data

Use file `fresh_coal_feed_fluid_injection.sff` **Edit**

Use specified values

Velocity: 0 m/s

Mass flow: 0 kg/s

Temperature: 0 K

Fluid composition: **Define fluids**

Locations (0 of 0 injections are active)

Name	On/Off	X (m)	Y (m)	Z (m)	nx	ny	nz	Particle Mass Weight	Particle Temp Multiplier	Fluid Mass Weight	Fluid Temp Multiplier
1	<input type="checkbox"/> Off										

Add Row **Delete Row** **Check Table** **Import** **Export** Particle weight sum 0 Fluid weight sum 0

Reference Grid **Expand Locations Table** **OK** **Cancel**

Fluid Injection Boundary Conditions Editor

Time (s)	On/Off	Temperature (K)	Velocity (m/s)	Mass Flow Rate (kg/s)
1 0	<input checked="" type="checkbox"/> On	500	5	5e-3
2	<input checked="" type="checkbox"/> On			

Add Row **Delete Row** **Check Data** **Graph** **Update Simulation**

File: `fresh_coal_feed_fluid_injection.sff` **Save** **Save As** **Close**

Applied materials

Applied materials

Fractions sum to: 1.0

ID	Material	State	Fraction
000	N2	G	0.77
001	O2	G	0.23

Add material **Edit** **Delete**

Fraction type

Mass fraction Mole fraction

OK **Cancel**

Fresh Coal Feed Injection

- Specify the location of the fresh coal feed nozzle.
- Enter an appropriate **Name** for the injection point.
- Select “**On**”.
- Enter the x,y,z location and the directional vector for the nozzle.
- Enter a value of “1” for:
 - Particle Mass Weight
 - Particle Temp Multiplier
 - Fluid Mass Weight
 - Fluid Temp Multiplier
- Click **OK**.

Injection BC Editor

Injection name: Fresh_coal_feed

Comment:

Particle/Tracer Injection
 Use BC Connector data
 Use file `particle_injection.sff` Edit 📄
 Use specified values

Injection type
 Type: Particle 📄
 Species: 002 - fresh coal feed

Velocity: 0 m/s
 Mass flow: 0 kg/s
 Temperature: 0 K
 Number density: 125

Angle Expansion
 θ_{E1} : 15 ° θ_{E2} : 15 ° 📄

Angle Orientation
 α_{E1} : 0 ° 📄

Flux plane options
 Flux plane name: FLUXBC_fresh_coal_feed 📄
 Gas species flux plane behavior: No Output
 Subdivide by radius Radius divisions: 100
 Output raw particle data
 Fluid Injection
 Use BC Connector data
 Use file `fresh_coal_feed_fluid_injection.sff` Edit 📄
 Use specified values

Fluid composition
 Velocity: 0 m/s
 Mass flow: 0 kg/s
 Temperature: 0 K
Define fluids 📄

Locations (1 of 1 injections are active)


Name	On/Off	X (m)	Y (m)	Z (m)	nx	ny	nz	Particle Mass Weight	Particle Temp Multiplier	Fluid Mass Weight	Fluid Temp Multiplier
1 Feed	<input checked="" type="checkbox"/> On	1.5	0	1.75	-1	0	-1	1	1	1	1
2	<input type="checkbox"/> Off										

+ Add Row - Delete Row ✓ Check Table 📄 Import 📄 Export Particle weight sum: 1 Fluid weight sum: 1

📄 Reference Grid 🔍 Expand Locations Table OK Cancel

Fresh Coal Feed Injection


- Before continuing with the project setup, check the location of the nozzle by running the simulation for a single time step.
- Under **Run**, click **View Boundary Conditions**.




Tip: To view only the nozzle, click on **Display** → **Polygons** in the Gmv window, select **SolidJet** and **FluidJet** only, and click **Apply**.

Separate the Air and Steam BCs

- One simplification that was made in the Tuesday gasifier was the exclusion of the gas sparger geometry.
- Now that we are including the sparger, it is necessary to separate the fluidizing air (N_2+O_2) from the steam.
- Keep the bottom-most flow BC as a uniform air distributor.
 - **Review the Process Sheet** (slide 3) for air mass flow rate and temperature.
- Create an injection BC on the bottom surface of the sparger, and introduce 100% steam at this location through 204 nozzles.
 - See next slide for details.
- **NOTE:** An injection BC requires that the user input both the mass flow rate and a velocity. Often, the mass flow information only is given and velocity must be calculated based on nozzle diameter.



Air ($N_2 + O_2$)
introduced through
flow BC on bottom
surface of vessel



Steam introduced
through 204
injection points
located on the
sparger

Steam Injection BC

- Create a new injection BC for the steam sparger by clicking on **Add** on the **Injection BC** page.
- Enter an **Injection Name** and **Flux Plane** name.
- Select **Fluid Injection**.
- Use a transient (.sff) file to specify the fluid mass flow rate:
 - Click on **Edit**
 - Enter the appropriate values
 - **Save** the file using a descriptive name
- Specify the fluid composition as 100% steam.

The screenshot shows two windows from a software interface. The top window is the 'Injection BC Editor' and the bottom window is the 'Fluid Injection Boundary Conditions Editor'.

Injection BC Editor:

- Injection name:** Steam_sparger
- Flux plane name:** FLUXBC_steam_sparger
- Injection type:** Particle
- Species:** 001 - initial char in bed
- Fluid Injection:** Checked
- Use file:** BC_sparger_injection.sff
- Buttons:** Edit, Define fluids

Fluid Injection Boundary Conditions Editor:

Time (s)	On/Off	Temperature (K)	Velocity (m/s)	Mass Flow Rate (kg/s)
1 0	On	900	0	0
2 0.1	On	900	10	0.296
3	On			

File: BC_sparger_injection.sff

Buttons: Add Row, Delete Row, Check Data, Graph, Update Simulation, Save, Save As, Close

Steam Injection BC

- Creating and editing large sets of location and direction data is most conveniently done in Excel, Open Office, or other spreadsheet application:
 - Data from the **Locations** table can be exported as a comma-separated value (CSV) file by clicking on the **Export** button in the Barracuda VR GUI
 - Once the file has been edited, it can be easily imported into the locations table
- To save time, a CSV file containing the locations and directions of the 204 nozzles has already been created for this problem.
- Click on **Import** and select the file `sparger_injection_bc_locations.csv`, which is located in the “my_setup” folder.
- Click **OK** in the import dialog.

The screenshot illustrates the workflow for importing a CSV file into the Barracuda VR GUI. The main window, 'Injection BC Edit', shows the 'Locations' table with one row active. The 'Import' button is highlighted with a red arrow. An 'Open File' dialog is open, showing the file 'sparger_injection_bc_locations.csv' selected in the 'my_setup' folder. A 'Dialog' window is also open, showing a preview of the CSV data with the 'OK' button highlighted by a red arrow.


	1	2	3	4	5	6	7	8	9	10	11	12
1	NE_1	On	0.1	1.25	0.15	0	1	-1	1	1	1	1
2	NE_2	On	0.2	1.25	0.15	0	-1	-1	1	1	1	1
3	NE_3	On	0.3	1.25	0.15	0	1	-1	1	1	1	1
4	NE_4	On	0.4	1.25	0.15	0	-1	-1	1	1	1	1

Steam Injection BC

- Once the locations table has been imported, click **OK** and run the simulation for a single time step to check the location of the nozzles.



- Tip:** To view only the nozzle, click on **Display** → **Polygons** in the Gmv window, select **SolidJet** and **FluidJet** only, and click **Apply**.




Thermal Wall BCs: Heating Coils

- The gasification process requires input of heat. We will define thermal wall BCs on the heating coils, setting the temperature in a transient input (.sff) file.
- Specifying the locations of thermal walls is very similar to that of flow BCs.
- Use **Normal to surface** and avoid placing any thermal wall BCs on the outer vessel wall or cyclone diplegs. **Hint:** you will have to define at least three separate thermal wall BC blocks.
- Keep the default option of outputting thermal wall heat transfer information to a transient data file. This will allow us to see how much heat is being provided by the heating coils.
- **Run Solver Setup (for 1 time-step)**, and verify that the thermal wall BCs are applied correctly.

 **1** Run Solver Setup (1 time step)

 View Boundary Conditions



Chemistry

- The gasification reactions listed on Slide 5 need to be input to the chemistry section.
- For this training problem, we will use stoichiometric, volume-average chemistry.
- Definitions and units for the terms used on Slide 5 are:
 - m_C = mass concentration of carbon (kg/m^3)
 - T = fluid temperature (K)
 - θ_C = carbon volume fraction
 - $[X]$ = mole concentration of species X ($\text{mol X} / \text{m}^3$ gas volume)

Barracuda Virtual Reactor with Chemistry - 17.3.0 - /C:/training/5_Wednesday_Gasifier/my_setup/Tuesday_Gasifier.prj

File View Setup Run Graphics and Output Post-processing Help

Project Tree

- Thermal Wall BCs
- Passive Scalar BCs
- BC Connections
- Secondary Feeds
- Secondary Exits
- BC Connectors
- Chemistry
 - Rate Coefficients
 - Reactions
- Numerics
- Time Controls
- Data Output
 - Flux Planes
 - GMV Output Options
 - Average Data
 - 2D Plot Data
 - Transient Data
 - Wall Erosion

Chemistry Rate Coefficients Manager

ID	Name	Reaction Type	Coefficient Type	Expression	Comment
00	k0	Volume-Average	Arrhenius Chem Rate	$6.36 T^{11} e^{(-22645 / T)} m_C^{11}$	Steam gasification (forward)
01	k1	Volume-Average	Arrhenius Chem Rate	$0.0005218 T^{12} e^{(-6319 / T + -17.29)} m_C^{11}$	Steam gasification (reverse)
02	k2	Volume-Average	Arrhenius Chem Rate	$6.36 T^{11} e^{(-22645 / T)} m_C^{11}$	CO2 gasification (forward)
03	k3	Volume-Average	Arrhenius Chem Rate	$0.0005218 T^{12} e^{(-2363 / T + -20.92)} m_C^{11}$	CO2 gasification (reverse)
04	k4	Volume-Average	Arrhenius Chem Rate	$0.006838 T^{11} e^{(-8078 / T + -7.087)} m_C^{11}$	Methanation (forward)
05	k5	Volume-Average	Arrhenius Chem Rate	$0.755 T^{10.5} e^{(-13578 / T + -0.372)} m_C^{11}$	Methanation (reverse)
06	k6	Volume-Average	Arrhenius Chem Rate	$4.34e+07 T^{11} e^{(-13590 / T)} v_f C^{11}$	Combustion
07	k7	Volume-Average	Arrhenius Chem Rate	$7.68e+10 e^{(-36640 / T)}$	WGS (forward)
08	k8	Volume-Average	Arrhenius Chem Rate	$6.4e+09 e^{(-39260 / T)}$	WGS (reverse)

Tuesday_Gasifier.prj C:/training/5_Wednesday_Gasifier/my_setup

Barracuda Virtual Reactor with Chemistry - 17.3.0 - /C:/training/5_Wednesday_Gasifier/my_setup/Tuesday_Gasifier.prj

File View Setup Run Graphics and Output Post-processing Help

Project Tree

- Thermal Wall BCs
- Passive Scalar BCs
- BC Connections
- Secondary Feeds
- Secondary Exits
- BC Connectors
- Chemistry
 - Rate Coefficients
 - Reactions
- Numerics
- Time Controls
- Data Output
 - Flux Planes
 - GMV Output Options
 - Average Data
 - 2D Plot Data
 - Transient Data
 - Wall Erosion
 - Particle Attrition
 - Raw Data
 - Population Data
 - Solver Output Units


Chemistry Reactions Manager

ID	Reaction Type	Rate	Equation	Comment
00	VA: Stoichiometric	Equation: $C(S) + H_2O \Rightarrow CO + H_2$ R00 = $(k0[H_2O])$		
01	VA: Stoichiometric	Equation: $CO + H_2 \Rightarrow C(S) + H_2O$ R01 = $(k1[H_2][CO])$		
02	VA: Stoichiometric	Equation: $C(S) + CO_2 \Rightarrow 2 CO$ R02 = $(k2[CO_2])$		
03	VA: Stoichiometric	Equation: $2 CO \Rightarrow C(S) + CO_2$ R03 = $(k3[CO]^2)$		
04	VA: Stoichiometric	Equation: $0.5 C(S) + H_2 \Rightarrow 0.5 CH_4$ R04 = $(k4[H_2])$		
05	VA: Stoichiometric	Equation: $0.5 CH_4 \Rightarrow 0.5 C(S) + H_2$ R05 = $(k5[CH_4]^{0.5})$		
06	VA: Stoichiometric	Equation: $2 C(S) + O_2 \Rightarrow 2 CO$ R06 = $(k6[O_2])$		
07	VA: Stoichiometric	Equation: $CO + H_2O \Rightarrow CO_2 + H_2$ R07 = $(k7[CO]^{0.5}[H_2O])$		
08	VA: Stoichiometric	Equation: $CO_2 + H_2 \Rightarrow CO + H_2O$ R08 = $(k8[H_2]^{0.5}[CO_2])$		

Tuesday_Gasifier.prj C:/training/5_Wednesday_Gasifier/my_setup

Time Controls

- Leave the end-time at “100” s.
- When specifying an end-time, take into consideration the various physical time-scales of the system. How long will the fluidization take to become steady? How long will thermal effects take? How long should chemical equilibrium take?
- Leave the time-step at “0.01” s.
 - When running this more complex case with thermal and chemistry calculations, it is likely that a smaller time-step will be required to solve these additional equations.
 - Keep this initial guess of 0.01 s, but compare the time-step actually used by the solver during the run with that of the isothermal Tuesday gasifier.



GMV Output Options

- Since thermal and chemistry are now being incorporated into the model, it is important to review the data output settings. Make sure that all necessary output data is selected.

Barracuda Virtual Reactor with Chemistry - 17.3.0 - /C:/training/5_Wednesday_Gasifier/my_setup/Tuesday_Gasifier.prj

File View Setup Run Graphics and Output Post-processing Help

Project Tree

- Pressure BCs
- Flow BCs
- Injection BCs
- Thermal Wall BCs
- Passive Scalar BCs
- BC Connections
 - Secondary Feeds
 - Secondary Exits
 - BC Connectors
- Chemistry
 - Rate Coefficients
 - Reactions
- Numerics
- Time Controls
- Data Output
 - Flux Planes
 - GMV Output Options
 - Average Data
 - 2D Plot Data
 - Transient Data
 - Wall Erosion
 - Particle Attrition
 - Raw Data
 - Population Data
 - Solver Output Units
- Run
- Post-Run
- Plot Manager

General Mesh View Data Output Options

Please select Eulerian and Lagrangian data for export to the General Mesh Viewer (GMV). Only data selected here can be viewed during post-processing. Values inside parenthesis are the **field names** of the variables within GMV.

Output file interval

Plot interval: 0.2 s Number of files produced using current end time of 100s: 501

Eulerian (Cell) Output Data

<input checked="" type="checkbox"/> Particle volume fraction (p-volFra)	<input type="checkbox"/> Particle bulk density (p-dens)	<input type="checkbox"/> dp/dx (dp/dx)
<input checked="" type="checkbox"/> Fluid velocity (U, V, W)	<input type="checkbox"/> Turbulent viscosity (ViscTurb)	<input type="checkbox"/> dp/dy (dp/dy)
<input checked="" type="checkbox"/> Particle velocity (P_[xyz]Vel)	<input checked="" type="checkbox"/> CFL (CFL)	<input checked="" type="checkbox"/> dp/dz (dp/dz)
<input checked="" type="checkbox"/> Pressure (Pressure)	<input type="checkbox"/> Particle species (Species)	<input type="checkbox"/> Particle mass flux (P_[xyz]Mass)
<input type="checkbox"/> Dynamic pressure (DynPres)	<input checked="" type="checkbox"/> Fluid temperature (f-Temp)	<input type="checkbox"/> Fluid mass flux (F_[xyz]Mass)
<input checked="" type="checkbox"/> Fluid density (F-dens)	<input checked="" type="checkbox"/> Particle temperature (p-Temp)	<input checked="" type="checkbox"/> Wall heat transfer (wallHeat)
<input checked="" type="checkbox"/> Cell indices (i, j, k)	<input checked="" type="checkbox"/> Cell volume (cellVol)	

Lagrangian (Particle) Output Data

<input checked="" type="checkbox"/> Particle volume fraction (VolFrac)	<input checked="" type="checkbox"/> Particle material (Material)	<input checked="" type="checkbox"/> Velocity (vel[xyz])
<input checked="" type="checkbox"/> Particle speed (Speed)	<input type="checkbox"/> Particle density (Density)	<input checked="" type="checkbox"/> Residence time (ResTime)
<input checked="" type="checkbox"/> Particle radius in microns (rad)	<input checked="" type="checkbox"/> Particle species (Species)	<input type="checkbox"/> Residence time by species (ResTime##)
<input type="checkbox"/> Constant color (Particle)	<input checked="" type="checkbox"/> Unique particle ID (pid)	<input checked="" type="checkbox"/> Temperature (Temperat)
<input type="checkbox"/> Drag (drag)	<input type="checkbox"/> Liquid fraction total (liqFrac)	<input type="checkbox"/> Liquid mass total (liqMass)
<input type="checkbox"/> Cloud mass (cldMass)	<input type="checkbox"/> Particles per cloud (npCloud)	<input type="checkbox"/> Particle mass (mass)

Gas Species

<input checked="" type="radio"/> Mass fraction (<species>.mf)	<input type="radio"/> Mole fraction (<species>.nf)
<input type="radio"/> Mass concentration (<species>.mc)	<input type="radio"/> Mole concentration (<species>.nc)


Options

<input type="checkbox"/> Compress graphics output (not common)
<input type="checkbox"/> Generate predefined GMV attribute files

Tuesday_Gasifier.prj C:/training/5_Wednesday_Gasifier/my_setup


Average Data

- Time-average data is very useful when analyzing particle-fluid systems. Fluidized beds, for instance, are dynamic by nature and will not reach a traditional “steady-state” condition.
- Start time-averaging at “20” s.
- Since we have now turned on thermal and chemistry, be sure to check the boxes for Fluid temperature, Particle temperature, and Gas species.




Transient Data

- Transient data points can be defined to monitor many different variables during the course of a simulation.
- For this model, define several transient data points to monitor the fluid temperature (**Fluid temp**) at different elevations in the bed.
- Note that transient data points can be specified using either **xyz** or **Node** locations. If you choose to use xyz, the locations must be specified in units of meters. Use reference grid if needed.




Define 4 transient data points along the central axis of the bed to monitor fluid temperature.

Check that the transient data points are at the desired locations.



Check Model Setup

- **Save** your project.
- Run the simulation for a single time-step.
- Check the boundary conditions.
 - Are the flow BCs applied correctly?
 - Are the pressure BCs applied correctly?
- Check the initial conditions.
 - Are particles initialized properly? Do you have the correct initial bed mass?
- Do you have all desired variables in the Gmv.00000 file? If you forgot any output variables, now is the easiest time to add them!
- Review the project setup with the instructor, and start the project running when you are confident it is set up correctly.



"Particle Feed Deficit" Warning

- Early in the simulation, a warning will be written to the solver run window

```

Barracuda Virtual Reactor - 17.3.0 - pre_setup/Wednesday_Gasifier.prj" - cpfd.x.17.exe -omp 7 -gpu Wednesday_Gasifier.prj
# Decrease dt from CFL. Old = 1.000e-02 New = 8.000e-03 (10 30 4)
2.50000e-01 8.000e-03 003 2.86e-08 008 1.60e-08 008 1.49e-08 008 2.18e-08 009 1.25e-06 856 9.98e-08 1.53 0.00 107 0 0 2
2.58000e-01 8.000e-03 003 1.87e-08 007 6.78e-08 007 9.99e-08 007 6.47e-08 009 9.70e-08 684 9.75e-08 1.28 0.00 108 0 0 2
2.66000e-01 8.000e-03 003 1.84e-08 007 2.65e-08 007 3.41e-08 007 8.00e-08 008 5.90e-07 777 9.88e-08 1.22 0.00 120 0 0 2
2.74000e-01 8.000e-03 003 1.85e-08 007 8.10e-08 008 7.49e-09 007 4.90e-08 010 1.14e-06 729 9.97e-08 1.17 0.00 132 0 0 2
2.82000e-01 8.000e-03 003 2.07e-08 007 8.04e-08 007 5.20e-08 007 0.07e-08 010 7.81e-07 760 0.84e-08 1.08 0.00 129 0 0 2
Injection [FLUXBC_fresh_coal_feed]:[Feed] @ ( 1.500e+00, 0.000e+00, 1.750e+00) has particle feed deficit.
A mass of 1.997e-01 kg needs at least 1.911e-01 seconds to be recovered,
given the specified [1.00000e+00 kg/s] and current [1.003408e+00 kg/s] rates of feed.
2.90000e-01 8.000e-03 003 3.75e-08 007 4.85e-08 007 4.14e-08 007 2.81e-08 010 5.08e-07 716 9.93e-08 0.97 0.00 122 0 0 2
2.98000e-01 8.000e-03 003 2.17e-08 007 2.95e-08 007 2.42e-08 007 2.98e-08 009 2.62e-06 686 9.86e-08 1.19 0.00 117 0 0 2
3.06000e-01 8.000e-03 003 2.54e-08 007 2.61e-08 007 1.69e-08 007 1.50e-08 008 1.57e-06 666 8.94e-08 1.00 0.00 77 0 0 2

t dt Vol Vol u u v v w w h h p p CFL dT/dt Low Med Hi R
s s itr err itr err itr err itr err itr err itr err itr
-----
3.14000e-01 8.000e-03 003 3.77e-08 007 2.54e-08 007 1.78e-08 007 2.29e-08 009 1.21e-07 651 9.96e-08 1.06 0.00 39 0 0 2
    
```

- This type of warning indicates that a particle feed BC cannot meet the specified mass flow rate. This can happen when:
 - Trying to feed into a cell that already has a high concentration of particles (such as the initial packed bed in the Wednesday Gasifier setup)
 - Trying to feed a particle mass flow rate that is physically too high
- Barracuda always honors the close-pack volume fraction, and will not feed particles if the cell is too full of particles

Recovering from Particle Feed Deficit

- The solver keeps track of the mass deficit, and tries to recover the mass at a later time if possible
- In the Wednesday Gasifier, the particle mass feed deficit is able to recover by about $t = 0.5$ s

